



**(51) International Patent Classification<sup>7</sup>: F03B 13/18,**  
15/00

**(21) International Application Number:** PCT/GB2004/003113

**(22) International Filing Date:** 16 July 2004 (16.07.2004)

(25) Filing Language: English

**(26) Publication Language:** English

**(30) Priority Data:**  
0316869.7                      18 July 2003 (18.07.2003)      GB

**(71) Applicant and**

(72) Inventor: KELLY, Hugh-Peter, Granville [GB/GB]; 47 Crowstone Road, Westcliff on Sea, Essex SS0 8BG (GB).

**(81) Designated States (unless otherwise indicated, for every kind of national protection available):** AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,

CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,  
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,  
PII, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,  
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,  
ZW.


**(84) Designated States (unless otherwise indicated, for every kind of regional protection available):** ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Published:**

— with international search report

***For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.***

(54) Title: METHOD OF OPERATION FOR A SELF-PROTECTING WAVE ENERGY CONVERSION PLANT



**(57) Abstract:** A wavefarm (10) comprises a multiplicity of wave energy converters, comprising linear generators (19, 20, 21) and (22) which are driven by floats immersed in the sea, (14). In normal wave conditions, all of the generators supply a land line (17) via a control unit (18). In the event of inclement conditions, one or more of the generators are switched to linear motors, and these are then powered by those generators remaining in the sea, to withdraw their floats into protective cavities (23). The process is repeated sequentially until all but the last one or few of the generators have withdrawn their floats. Finally, these last are withdrawn by connecting them to an alternate power source eg a battery, (24), again via the control unit (18).